CCESSIBILITY FOR HXME & PUBLIC BUILDINXS

Aritco Home & Public Access Lift

Datasheet 2021

Aritco Access Lift is designed to make your home as well as public and commercial buildings accessible for everyone. Practical and smart with sizes for all needs. The lift expresses Scandinavian design and features a backlit panel and lit handlebar. With an option to personalize it with details such as glass walls, a range of various colors and different materials.

Advantages offered by Aritco Access Lift:

- Design, sizes and options created for a home environment
- Minimum interventions in the house
- Option for a "half-height door" on the top floor
- 'A' rated energy consumption according to VDI4707
- 95% recyclable materials
- Patented screw/nut technology (no oil that can leak)
- The lowest maintenance and operating costs on the market
- Equipped with our SmartSafety system with safety features for home environments.

For more information please visit: www.aritco.co.th











CONTACT US: 088-333-2020 088-333-5050 088-333-9090

ARITCO (THAILAND) CO., LTD.

Bang Kho Laem, Bangkok Thailand 10120

Tel: 02 - 408 - 0200 Fax: 02 - 638 - 8877

Email: Sales@aritco.co.th Website: www.aritco.co.th

Facebook.com/AritcoThailand



ARITCO ACCESS LIFT

LIFT COLOUR

Can be painted in any RAL colour from the Chart K7 classic chart (except for pearl and fluorescent colours).

GLASS -----

2 different glass types to choose from.







8 different floorings to choose from.



Dark Grey, Vinyl



Light Grey, Vinyl



Checker Stud Grey,



European oak, Vinyl



Aged Oak, Vinyl




Checker Stud Black, Rubber



1160 1300 1040 900 800


Size: 900 x 1040 mm Rated load: 250 kg / 2 pers.

Wheelchair: -




Size: 900 x 1480 mm

Rated load: 410, 500 kg / 5, 6 pers. Wheelchair: A or B with attendent*



Size: 1000 x 1480 mm


Rated load: 410, 500 kg / 5, 6 pers. Wheelchair: A or B with attendent*




Size: 1000 x 1980 mm Rated load: 500 kg / 6 pers. Wheelchair: A or B with attendent*

1400 800 1280 900

Size: 900 x 1280 mm Rated load: 410 kg / 5 pers. Wheelchair: Lone user or type A*




Size: 1000 x 1280 mm Rated load: 410 kg / 5 pers. Wheelchair: Lone user or type A*



Size: 1100 x 1480 mm

Rated load: 410, 500 kg / 5, 6 pers.


Wheelchair: A or B with attendent, adjacent entry*



Size: 1100 x 1580 mm Rated load: 500 kg / 6 pers. Wheelchair: A or B with attendent, adjacent entry*

Product summary

TOP HEIGHT Minimum



Power supply:

230 V 1-phase: Max 0,15 m/s 400 V 3-phase: Max 0,25 m/s

(outside Europe)



SYSTEM

Patented screw and nut system 2.2 kW motor



INSTALLATION

Recessed installation 50 mm below floor

Installed directly on floor with 50 mm ramp

TRAVEL HEIGHT

250 - 13000millimeter

CONTROL FROM CARRIER CONTROL PANEL

Hold to run - press and hold For installations outside Europe One touch operation



NUMBER



(press one time)

WARRANTY

Aritco access lift comes with a 24 month warranty. The screw and nut assembly has a 10 year warranty.



TECHNICAL COMPLIANCE

European Machine directive 2006/42/EC European standard EN 81-41

Emergency lowering: Battery-powered

^{*} National guidelines may apply. Wheelchair Type A and B according to EN 12183/EN 12184.